

# CHAPEL OFF CHAPEL

## THE CHAPEL

### LIGHTING EQUIPMENT

#### DESK

ETC GIO @5 (4,096 Channels)

#### DIMMERS & DATA

9 x LSC GEN VI 12 channel wall dimmers  
2 x Chauvet Net-X II  
1 x Enttec Ethergate Mk3

#### PROFILE

7 x Chauvet Ovation E-930VW (15°–30° lens)  
6 x Chauvet Ovation E-930VW (25°–50° lens)  
8 x Chauvet Ovation Rêve E-3 (25°–50° lens)

#### FRESNEL

10 x Chauvet Ovation E-915VW (16°–42° lens)  
6 x Silver Star FREZNO ze-3 (18°–60° lens)

#### LED PAR & BATTEN

9 x TourPro SlimPar 18 RGBWA+UV 25°  
6 x Elation SixBar 1000  
4 x Chauvet Shocker 2

#### MOVING YOKE

3 x Robe T1 Profile  
2 x Claypaky Axcor 300 Profile  
4 x Ayrton Merak Wash  
4 x Chauvet Maverick MK2 Wash

#### HAZER/FX

*\*Additional charges and needs to be booked in*  
\* Hazer – Unique 2  
\* Fan – AF3 FAN with DMX

#### RIGGING

\* Mirror Ball with motor  
\* 4 x 2.5m booms with 500 x 500 base plate  
\* 8 x boom arms  
\* 2 x 3m tri truss with 500 x 500 base plate  
\* 2 x 3m tri truss no Base plate  
4 x Eurotruss 250MM T-JOINT  
4 x Eurotruss 1m Extension tube to fit T-JOINT  
4 x Eurotruss 500mm Extension tube to fit T-JOINT

#### LIGHTING BARS

The lighting rig consists of seven motorised lighting bars, the maximum point loading is 50kg and an overall bar maximum of 250kg. Each lighting bar has 14 dimmer outlets and its own DMX universe.

#### LIGHTING OUTLETS:

108 dimmer outlets in The Chapel  
14 dimmer outlets on each bar  
6 dimmer outlets on each side of the stage  
2 dimmer outlets at lighting desk

#### POWER

3 x 10amp hot circuits on each lighting bar  
1 x 10amp double outlets on each side of the stage  
4 x 10amp outlets at the control desk  
1 x 32amp 3phase outlet on P  
1 x 32amp 3phase outlet outside of the building

#### VENUE

Width Wall-to-Wall	12 metres
Depth Wall-to-Wall	21 metres
Grid Height	5.7 metres
Roof Beam Height	5 metres

Stage Area @ 240 capacity  
Width wall-to-wall 12 metres  
Depth wall-to-seats 8 metres